AKRON MOTORCYCLE 4T® SAE 20W-50

4T Motorcycle Oil



Product Description

Akron Motorcycle 4T SAE 20W-50 is a specially lubricant for all type 4 stroke motorcyles. Formulated with selected base stock and additives package that offers maximum protection for your motorcycle's engine against high temperature deposits and wear.

Its meets with JASO MA2 and API Service SL.

Specification

API Service SL. JASO MA2.

Benefits

- Continuous protection of engine and transmission.
- Reduce engine deposits formation.
- Good gear and wet clutch performance.
- Superior high temperature oil consumption and oxidation control.

Applications

Akron Motorcycle 4T SAE 20W-50 is recommended for all 4-stroke motorcycles and ATV (All Terrain Vehicles).

It meets with JASO MA2 and API Service SL.

Note: Do not apply on fuel tank or mix with fuel.

Typical Properties

Test	ASTM Method	Results
Product Code		0192
Color	D 1500	L 4.5
Flash Point, °C	D 92	233
Cold Cranking Simulator @ -15°C, Ccs	D 5293	6900
Kinematic Viscosity at 100°C, cSt	D 455	20.5
Viscosity Index	D 2270	133
Pour Point, °C	D 97	-15

Caution

Avoid long contact with skin. Extensive studies on the effect of oil derived hydrocarbons, which are the base of all types and trademarks of lubricant oils, have shown that these are harmful and can cause damage in humans. In case of eye contact, IMMEDIATELY flush eyes thoroughly with water and seek medical assistance. Keep all empty containers away from heat since emanating vapors are health hazardous.

Do not pollute. Do not pour used oil in drains or sewers. Empty containers of all oil residues, since these are soil and water contaminants.



Don't pollute; protect the environment by disposing of used containers, oils and fluids at authorized sites.

Verify that your service provider complies with environmental guidelines for fluids disposal.

Issue Date: December 29, 2014