

SN SAE 5W-30

High Performance Full Synthetic Motor oil



Description

Akron Spitzen SN SAE 5W-30 is formulate using synthetic base oils carefully selected, and special additives package that meet the most important technology standards of automobile industry, making it the more advanced product of its type. It meets API SN Service categorie and BMW (Longlife 04), Mercedes Benz (MB 229.51) and Volkswagen (VW 502.00 / 505.00).

Specification

VW 502.00 / 505.00	ACEA A5/B5-04
MB 229.51	ACEA C2-10
ACEA A3/B4-04/A3/B3-04	ACEA C3-10
ACEA A1/B1-04	API SN

Benefits

- · Certified by main german OEM's.
- Excellent thermal and oxidation stability.
- · Low oil consumption.
- Excellent fuel economy.
- Outstanding wear protection and engine cleanliness.
- Excellent dispersion of soot.
- High performance at extreme temperatures.
- Low viscosity.
- · Low volatility.
- Superior oil change intervals than mineral oil; up to 15,000 Km.

Applications

Akron Spitzen SN SAE 5W-30 is recommended for new or recent model vehicles, turbocharged, etc. That operates under severe service conditions and is exposed to a wide gamma of climate conditions. It meets API SN Service Categorie.

It's certified by Mercedes Benz (MB 229.51), BMW (Longlife 04) and Volkswagen (VW 502.00 / 505.00.

Typical Properties

Test	ASTM Method	Results
SAE Grade		5W-30
Product Code		0103
Appearence	Visual	Brilliant
ASTM Color	D 1500	2.5
Density @ 20°C	D 1298	0.875
Pour Point, °C	D 97	-36
Kinematic Viscosity @ 40°C, cSt	D 445	65
Kinematic Viscosity @ 100°C, cSt	D 445	11.5
Viscosity Index	D 2270	170
Low Temperature Viscosity	D 5293	5900
(CCS) @ -30°C, cP		
Flash Point, °C	D 92	202
TBN mg KOH/g	D 2896	7.4

Caution

Avoid prolonged contact with skin. Wide studies have been efected concerning the effect of petroleum derivate hydrocarbons, which constitute oil lubricant's base of any brand or type and it has been found that it can harm human being. If, accidentally lubricant oil falls into the eyes, wash immediately your eyes with abundant water and get medical assistance.

Do not use or expose empty vessels to the heat, generated vapors are harm for health and might be breathed.

Do not pollute. Do not throw used oil to the environment, or leave oil waste into the vessels, these wastes might pollute water and soil.

Available in:

• Bottle 1 L

• Drum 208 L





Don't pollute; protect the environment by disposing of used containers, oils and fluids at authorized sites. Verify that your service provider complies with environmental guidelines for fluids disposal.

Issue Date: April 7, 2015

www.akron-spitzen.com